



FORAGE WAGON

CENTRE FEED

All Giltrap Centre Feed Wagons have a feed control chute, to deliver feed onto the ground between the axles. This model is ideal for feeding longer chopped grass silage in the paddock.

Call 0800 804 458 to find your local dealer.

To view the full list of features and optional extras, visit www.giltrapag.co.nz.

KEY FEATURES

- Ladder, mudguards/walkways and LED tail lights fitted
- Double chassis ready for scales
- Variable elevator load sensing
- Stainless steel sides for corrosion and wear resistance
- Mesh front screen and back gate for good visibility
- Self-releasing back gate – opens automatically when bulk unloading
- Central greasing system for difficult-to-access bearings
- Bolt-on floor and elevator bars for simple maintenance
- Cast iron bearings for long life
- 35mm treated T&G pine floor for extra durability

OPTIONAL EXTRAS

- Wireless radio frequency feed rate control system
- Wireless electronic load scales
- Single or tandem axle available on some models
- Different wheel sizes
- Brakes
- Quick hitch stand
- Hydraulic jack
- Axle raising blocks
- Sprung/steering axles



Heavy cast sprockets and hi-tensile calibrated chains are used for the floor and elevator assemblies.



Wagon hydraulics incorporate elevator load sensing, belt speed adjustment, floor motor relief valve and manual or auto feed rate control.



All of the difficult access greasing points are conveniently mounted at a central point on the exterior for easy maintenance.



A breakaway latch protects the rear gate and is useful for bulk unloading during harvesting.



The feed control chute on centre feed wagons directs feed from the elevator onto the ground between the axles in a controlled row.



Hydraulic drum brake front axles are an option for all wagons. Controlled from either the remote hydraulic service or powered from the tractor brake kit if fitted.

MODEL	RF9C	RF11C	RF13C	RF16C	RF21C
Overall Length	6.075m	6.075m	7.475m	7.475m	9.200m
Overall Width	2.530m	2.530m	2.750m	2.750m	2.800m
Overall Height	2.610m	2.790m	2.610m	2.790m	2.920m
Loading Height	2.200m	2.440m	2.200m	2.440m	2.570m
Bin Length	3.800m	3.800m	5.200m	5.200m	6.400m
Bin Height	1.230m	1.470m	1.230m	1.470m	1.60m
Bin Width	2.050m	2.050m	2.050m	2.050m	2.050m
Tare Weight	2370kg	2520kg	3190kg	3510kg	4550kg
Approx Cubic Capacity	9.0m ³	11.0m ³	13.0m ³	16.0m ³	21.0m ³
No. Floor Chains	2	2	4	4	4
Load Cells	4 x 5000kg	4 x 5000kg	6 x 5000kg	6 x 5000kg	6 x 5000kg
Jack Type	80mm screw	80mm screw	80mm screw	80mm screw	80mm screw
Axle Type	Tandem	Tandem	Tandem	Tandem	Tandem
Axle Size	60mm (6 stud)	70mm (6 stud)	70mm (6 stud)	80mm (8 stud)	90mm (8 stud)
Wheels	11.5/80 x 15.3	11.5/80 x 15.3	400/60 x 15.5	15.0/70 x 18	400/70 R22.5